


Vehicle History Report

VEHICLE DETAILS

Chassis number ¹ :	RC1-1009374	Title information ² :	1	Deregistered to Export	\bigcirc
Manufacture date:	2013-12-05		u _		_
Make:	HONDA	Accident / Repair:	I ⇒	No problem	
Model:	ODYSSEY	Odometer rollback:		No problem	0
Body:	DBA-RC1	Manufacturer	C		-
Grade:	ABSOLUTE	recall:	G	No problem	
Engine:	K24W	Safety grade ³ :	8	*****	\bigcirc
Drive:	2WD	Contamination			
Transmission:	AT	risk:	<u> </u>	No problem	v

This vehicle does not qualify for Buyback Guarantee

Average Market Price





About Buyback Guarantee

This CAR VX Vehicle History Report is based only on Information supplied to CAR VX, LTD and available as of 2024-11-07 02:28:58. Other information about this vehicle, including problems, may not have been reported to CAR VX, LTD. Use this report as one important tool, along with a vehicle inspection and test drive, to make a better decision about your next used car.

ACCIDENT / REPAIR HISTORY

Problem type	Reported	Date reported	Data source	Details	Airbag
Collision	Not reported				
Malfunction	Not reported				
Theft	Not reported				
Fire damage	Not reported				
Water damage	Not reported				
Hail damage	Not reported				

ODOMETER READINGS HISTORY

Date reported	Data source	Odometer reading (Km)
2020-11-18	MLIT	64400
2022-12-09	MLIT	82200

USE HISTORY



DETAILED HISTORY


Event date	Location	Odometer reading (Km)	Data source	Details
2013-12-05			HONDA	Manufactured
2013-12			MLIT	First registration
2020-11-18		64400	MLIT	Inspection
2022-12-09	Nagoya	82200	MLIT	Inspection
2024-10-24	Nagoya		MLIT	Last registration

MANUFACTURER RECALL HISTORY

Date reported	Data source	Affected part	Details			
Not reported						
Overall Collision Safety Ratings						
Driver	's seat	Front passeng	er's seat			

Points	Evaluation	Goal average	Points	Evaluation	Goal average
32.88	*****	91%	23.22	*****	97%

* In order to accurately differentiate between the evaluations of different vehicles, a standard is set based on current technology. Up to 6 points out of 12 is given level 1 and the rest of the range is divided up into equal parts, which are respectively assigned to level 2 (more than 6 points but 7.5 or less), level 3 (more than 7.5 points but 9 or less), level 4 (more than 9 points but 10.5 or less) or level 5 (more than 10.5 points).



VEHICLE SPECIFICATION

1st gear ratio	2nd gear ratio	
3rd gear ratio	4th gear ratio	
5th gear ratio	6th gear ratio	
Additional notes	Airbag position, capacity	
Body rear overhang	Body type	MV&1BOX
Chassis number embossing position	Classification code	44
Cylinders	Displacement	2350
Electric engine type	Electric engine maximum output	

Electric engine maximum torque		Electric engine power	
Engine maximum power	190ps(140kW)/6400rpm	Engine maximum torque	24.2kg • m(237N • m)/4000rpm
Engine model	K24W	Frame type	
Front shaft weight	1000	Front shock absorber type	
Front stabilizer type		Front tires size	215/55R17 94V
Front tread	1560	Fuel consumption	
Fuel tank equipment	55	Grade	ABSOLUTE
Height	168	Length	483
Main brakes type		Make	HONDA
Maximum speed		Minimum ground clearance	
Minimum turning radius	5.4m	Model	ODYSSEY
Model code	DBA-RC1	Mufflers number	
Rear shaft weight	820	Rear shock absorber type	
Rear stabilizer type		Rear tires size	215/55R17 94V
Rear tread	1560	Reverse ratio	
Riding capacity	7	Side brakes type	
Specification code	17637	Stopping distance	
Transmission type	AT	Weight	1820
Wheel alignment	2WD	Wheelbase	2900
Width	182		

GLOSSARY

¹ Chassis number – a unique identification number of the vehicle in Japan (same as VIN in the USA or Europe)

² Title information:

Registered – qualified for driving in Japan

Deregistered Temporarily – not qualified for driving in Japan, usually a temporary title during the ownership change

Deregistered Completely – not qualified for driving in Japan, the vehicle is determined to be scrapped Deregistered to Export – not qualified for driving in Japan , the vehicle is determined to be exported

³ Determining the overall collision safety performance evaluation – For the driver's seat, the results of the full-wrap frontal collision test, offset frontal collision test, and side collision test are added together and evaluated to 6 different levels. For the Frontal passenger's seat, the results of the full-wrap frontal collision test and the side collision test (results for the driver's or the front passenger's seat are used) are added together and evaluated to 6 different levels.

Regular vehicle inspection – All vehicles in Japan must undergo regular vehicle inspections (shaken). New cars need to be tested after three years, and then vehicles must be tested every two years thereafter. A vehicle inspection (shaken) is compulsory for all vehicles with an engine size over 250cc. It ensures that all vehicles on the road are properly maintained and safe to drive. The test also checks that vehicles have not been illegally modified; if they are found to have been modified, they are not allowed on the road.

⁴ **Use in the contaminated regions** – The Fukushima Daiichi nuclear disaster was a catastrophic failure at the Fukushima I Nuclear Power Plant on 11 March 2011, resulting in a meltdown of three of the plant's six nuclear reactors. As a result, some areas in the following prefectures were contaminated: Fukushima, Miyagi, Ibaraki, Tochigi.

⁵ Radioactive contamination test – radioactive contamination inspection that was started in July 2011 as a preventive measure for exporting contaminated vehicles from Japan. The inspection is being conducted since in all sea ports of Japan under the supervision of The Japan Harbor Transportation Association (JHTA).

MLIT - Ministry of Land, Infrastructure, Transport and Tourism.

⁶ Japan New Car Assessment Program – the Ministry of Land, Infrastructure, Transport and Tourism (MLIT) and the National Agency for Automotive Safety & Victims' Aid (NASVA) have taken measures for safety, one of which is to assess commercially available vehicles through a variety of safety performance tests and release the resulting information compiled into the "New Car Assessment Program". The objective of Japan New Car Assessment Program is to increase the use of safe automobiles by providing an environment in which users can easily select such vehicles. This also promotes the development of safer vehicles by automobile manufacturers. Neck injury protection for rear-end collision performance test , rear seat passenger's protection for frontal collision performance test and seat belt reminder for passengers evaluation test are started in FY2009.

⁷ **Braking Performance Tests** – Braking performance is determined by the shortness of the distance in which a vehicle can stop and the stability of the vehicle at the time of braking. This test is performed under wet and dry road conditions for a vehicle which has both a driver and a front passenger. The distance it takes for the vehicle to stop and the stability of the vehicle at the time of braking is evaluated for when the vehicle is stopped abruptly while traveling at a speed of 100km/h. The stopping distance and vehicle speed have been measured by using GPS since FY2009.

CAR VX, LTD DEPENDS ON ITS SOURCES FOR THE ACCURACY AND RELIABILITY OF ITS INFORMATION. THEREFORE, NO RESPONSIBILITY IS ASSUMED BY CAR VX, LTD OR ITS AGENTS FOR ERRORS OR OMISSIONS IN THIS REPORT. CAR VX, LTD FURTHER EXPRESSLY DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

 $\ensuremath{\mathbb{C}}$ 2014-2024 Car VX Limited. All rights reserved.